


# Or-Bolt




All Steel



## Key features

- ✚ Multi grip capability
- ✚ Weather tight joint
- ✚ High shear and tensile strength.
- ✚ The stem is mechanically locked.
- ✚ Large gap closing capability





**ORNIT BLIND RIVETS**

Kibutz Or Haner 79190, Israel

Tel: 972-8-6610222

Fax: 972-8-6611380




## OR-BOLT 65 - TYPICAL PERFORMANCE DATA

**MULTI-GRIP FLUSH BREAK  
SUPERIOR STRUCTURAL FASTENERS**

**P (PROTRUDING) HEAD  
( STEEL/STEEL), POSITIVE LOCK  
PULL MANDREL SELF PLUGGING**

**Or-Bolt**



SIZE	RIVET CODE	RIVET LENGTH L	GRIP RANGE G	A	D	E	H	M	BLIND SIDE PROTRUSION N
	J65140 P	14.0	2.0-9.5					56	25
6.5mm	J65190 P	19.0	8.9-15.9	4.00	6.50	2.6	13.0	62	30
	JS65190 P	19.0	2.0-15.9					65	35

RIVET CODE	SHEAR STRENGTH, N /kgf	TENSILE STRENGTH, N /kgf
J65140 P		
J65190 P	11280 / 1150	9810 / 1000
JS65190 P		

BODY MATERIAL	LOW CARBON STEEL
MANDREL MATERIAL	MEDIUM CARBON STEEL
RIVET FINISH	ZINC COATED, CLEAR PASSIVATION
MANDREL FINISH	ZINC COATED, YELLOW PASSIVATION
RECOMMENDED HOLE SIZE	6.6 - 6.9 mm

NOTES: 1) ALL SIZES ARE IN MM.

2) SHEAR AND TENSILE STRENGTH VARIOUS DUE TO DIFFERENT GRIP RANGE AND HOLE SIZE.

ORNIT BLIND RIVETS  
Kibbutz Or Haner, 79190  
ISRAEL

Tel: +972 (08)6610222

Fax: +972(08)6611380

<http://www.ornit.com>

